



TECHNICAL INFORMATION

Watts:	36
Lumens:	3960
Input Power:	AC:220-240V, 50Hz
Long Life:	20,000 Hours
Unit Color:	White
Body Type:	PP+FE
PF:	>0.9
LED Chip Type:	SMD
CRI:	>80
Operation Temperature:	-20°C to +40°C
Dimmable:	No
Beam Angle:	110°
Color Temperature:	4000K
Dimension:	595x595x30mm
lumens per watt:	110

2 IN 1 PANELS | LED LIGHTING

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide an extended multi-year warranty on our products, as well as detailed support.

FEATURES

- Powerful LED light source with lumen efficiency of 110 LM/W
- Backlit panel with 2IN1 Recessed and Surfaced Installation
- Fitted with high efficiency SMD LED Chips
- Strong and sturdy PP+FE body
- Easy to connect driver for quicker installation
- Suitable for offices, conference rooms, showrooms, lobbies, cabins, kitchens etc.



LISTING DETAILS

Ean Code: 3800170202054

PACKAGING

Gross Weight (Kgs):	2.33
Unit CBM:	0.017462
Dimension:	595x595x30mm

MASTER BOX PACKAGING

Box Qty: 6