

Product Spec Sheet



VT-49204 200W SMD FLOODLIGHT F-CLASS 6500K BLACK BODY



FEATURES

- High quality LED SMD chip and high power driver
- Comparing with traditional halogen floodlights it can save upto 80% Energy
- Constant current Integrated IC driver Built in driver no external power supply required
- Built Strong and durable with Aluminium Corrosion resistant design
- Suitable for building facades, sports facilities, industrial, commercial billboards, hoardings, parking lots etc.

TECHNICAL INFORMATION

| Dimmable: | No |
|------------------------|----------------------|
| Instant Start: | 0-100% in < 1s |
| CRI: | >70 |
| On/Off Cycles: | >15000 |
| Model: | VT-49204-B |
| Beam Angle: | 110° |
| Color Temperature: | 6500K |
| Watts: | 200 |
| Lumens: | 17600 |
| Input Power: | AC:220-240V, 50/60Hz |
| Unit Color: | Black |
| Color for Web: | White |
| Body Type: | Aluminium |
| Dimension: | 400x33x333mm |
| Operation Temperature: | -20°C to +40°C |
| PF: | >0.9 |
| LED Chip Type: | SMD |
| Energy Rating Label: | F (2021) |
| Energy Saving: | 80 Energy |
| Long Life: | 25,000 Hours |
| IP Rating: | IP65 |

IP65 STANDARD



LISTING DETAILS

| SKU: | 6734 |
|-----------------|---------------|
| Model: | VT-49204-B |
| EAN: | 3800157684453 |
| Commodity Code: | 94054210 |

PACKAGING

| Gross Weight (Kgs): | 2.98 0.0062 | |
|---------------------|----------------|--|
| Unit CBM: | | |
| Dimension: | 400x33x333mm | |

MASTER BOX PACKAGING

| Box Qty: | 5 | |
|------------------|-----|--|
| Qty Per Pallet: | 200 | |
| Length (Box) mm: | | |
| Width (Box) mm: | | |
| Height (Box) mm: | | |