

Product Spec Sheet



VT-49104 100W SMD FLOODLIGHT F-CLASS 6500K WHITE BODY



FEATURES

- High quality LED SMD chip and high power driver
- Comparing with traditional halogen floodlights it can save upto 80% Energy
- Constant current Integrated IC driver Built in driver no external power supply required
- Built Strong and durable with Aluminium Corrosion resistant design
- Suitable for building facades, sports facilities, industrial, commercial billboards, hoardings, parking lots etc.

TECHNICAL INFORMATION

Dimmable:	No
CRI:	>70
Body Type:	Aluminium
Color Temperature:	6500K
Model:	VT-49104-W
Watts:	100
Lumens:	8700
Input Power:	AC:220-240V, 50/60Hz
Unit Color:	White
Color for Web:	White
Dimension:	270x27x222mm
Operation Temperature:	-20°C to +40°C
Instant Start:	0-100% in < 1s
On/Off Cycles:	>15000
Beam Angle:	110°
PF:	>0.9
LED Chip Type:	SMD
Long Life:	25,000 Hours
IP Rating:	IP65
Energy Rating Label:	F (2021)
Energy Saving:	80 Energy







LISTING DETAILS

SKU:	6726
Model:	VT-49104-W
EAN:	3800157684378
Commodity Code:	94054210

PACKAGING

Gross Weight (Kgs):	1.26
Unit CBM:	0.002425
Dimension:	270x27x222mm

MASTER BOX PACKAGING

Box Qty:	10
Qty Per Pallet:	500
Length (Box) mm:	275
Width (Box) mm:	30
Height (Box) mm:	225