

## **Product Specification Sheet**



## **Technical Information**

| Instant Start: | 0-100% in lt1s              |     | Dimmable:              | Yes              |
|----------------|-----------------------------|-----|------------------------|------------------|
| Watts:         | 80                          |     | Warranty (Years):      | 3                |
| Lumens:        | 5600                        |     | PF:                    | >0.9             |
| Beam Angle:    | 120                         |     | CRI:                   | >80              |
| Body Type:     | Acrylic + Aluminium + Steel | eel | Operation Temperature: | -25 to +50°c     |
| Long life:     | 20,000 Hours                |     | Input Power:           | AC:100-240V/50HZ |
| LED Chip Type: | SMD2835                     |     | Sensor Compatibility:  | Yes              |
| IP Rating:     | IP20                        |     |                        |                  |

## **Features**

- Elegant chandeliers built using cutting edge technology with built in LED
- Dimmable and Non Dimmable Options
- Easy to Install Energy Efficient ~~~~
  - Warranty up to 3 Years
  - Strong built using Aluminium Steel Acrylic
  - Applications Residential Lighting, Hotels, Restaurants, Commercial Lighting etc



Suitable & Recommended for maximum daily use of 10-12 hours, usage beyond this would void the warranty

## Packaging

| Unit Details                    |        | Listing Details |               |
|---------------------------------|--------|-----------------|---------------|
| Gross Weight(GW) Kgs            | 3.432  | EAN Code        | 3800157624657 |
| Unit CBM                        | 0.0858 | Commodity Code  | 9405403990    |
| Master Box Packaging            |        |                 |               |
| Master Box Qty (Pcs Per Carton) | 1      |                 |               |
| Qty Per Pallet                  | 15     |                 |               |
|                                 |        |                 |               |

