



### TECHNICAL INFORMATION

Watts:	36
Lumens:	2880
Input Power:	AC:200-240V, 50/60Hz
Long Life:	20,000 Hours
Body Type:	Plastic + ABS
PF:	>0.9
LED Chip Type:	SMD
CRI:	>70
Operation Temperature:	-20°C to +40°C
Dimmable:	No
Beam Angle:	120°
Color:	6000K
Dimension:	1200x76x66mm

### F SERIES

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide extended multi-year warranty on our products, as well as detailed support.

*One brand, endless solutions..*

SKU: 6201 - 1406

[View more details](#)

### SMD LED'S

80% energy savings through modern LED technology

4  
FEET



### FEATURES

- Using high power SMD technology which makes it more reliable and durable
- Complete protection from water, dust and corrosion - IP65 Rated
- Designed for maximum efficiency & minimal glare
- Save up to 80% in electricity consumption compared to a fluorescent lighting fixture
- Long Lifespan, Low maintenance and energy saving
- Excellent heat dissipation
- Suitable for parking lots, warehouses, garages, storage docks, workshops etc.
- Recommended daily usage: 10 - 12 hours \*Exceeding recommended daily usage will void warrant

### PACKAGING

Gross Weight: 1.45  
Unit CBM: 0.00713124  
Dimension: 1200x76x66mm

### MASTER BOX PACKAGING

Box Qty: 12  
Length (Box) mm: 1250  
Width (Box) mm: 80  
Height (Box) mm: 80

### LISTING DETAILS

Commodity Code: 9405403990  
EanCode: 3800157603287

CE/EMC

CE/LVD

